


PREMIER SERIES

| | 1 | 2 |
|-------------------------------|------------------------|------------------------|
| Pixel Pitch | 10 | 8.3 |
| LED Type | SMD 3535 | |
| Module Size(WxH) | 320x300 | |
| Pixel Per Module | 32x30 | |
| Size(WxHxT) | 1280x900x120mm | 1000x750x90mm |
| Pixels | 128x90 | 120x90 |
| Material | Aluminum | Aluminum |
| Weight | 52 | 29 |
| Brightness | >6000 | 6000 |
| Processing depth | 14~16 | 14-16 |
| Display refresh rate | 2880~3840 | 1920 |
| Color Temperature | 3200-9300 | |
| Viewing angle(H) | 140 (-70 / +70) | |
| Viewing angle(V) | 70 (-20/+50) | |
| Drive type | 1/2 Scan | |
| AC Operating Voltage | 110/240 | |
| AC Input Frequency | 50/ 60 | |
| Power Consumption (Max./Avg.) | 677/225 | 750/250 |
| Storage Temperature | -40~+60 | |
| Operating Temperature | -20~+50 | |
| Storage Humidity | 10%-90% | |
| Operating Humidity | 10%-90% | |
| IP Rating (Front / Rear) | IP65/IP54 | IP65/IP54 |
| Module Maintenance | Front | Front |
| PSU & Others Maintenance | Rear | Rear |
| Panel Installation Type | Perimeter Installation | Perimeter Installation |



Outdoor SMD HD

A true champion in every league
Designed to international standards,
manufactured to precise perfection
Perimeter displays that will guarantee you a
place in the final



Front view



The soft mask

- 90° Rotation for emergency gates
- Collision protection for players
- High protection grade
- Dual data and power inputs insure uninterrupted play during live events
- EMC approval
- Dust proof and waterproof
- Fibre optic compatible for data runs over 100m
- Flight cases included for convenient storage and transport

OCULUS SPORT

| | |
|-----------------------------------|--------------------------|
| Pixel Pitch | 2.9 |
| Pixel Density | 113260 |
| Viewing Angle (H/V) | 160/160 |
| Brightness | 1200 |
| Grey Level | 14/16 |
| Refresh Rate | 960/1920/3840 |
| Brightness Adjustment | Manual/Auto/Programmable |
| Module Size (w x h) | 250 x 250 |
| Module Size (w x h) | 9.84 x 9.84 |
| Panel Size (w x h x d) | 500 x 500 90 |
| Panel Size (w x h x d) | 19.69 x 19.69 x 3.54 |
| Panel Resolution | 168 x 168 |
| Panel Type and Material | Die-cast aluminum |
| Panel Weight | 8 |
| Hanging Panel Quantity (Vertical) | <20 |
| Avg. Power Consumption | 250 |
| Max. Power Consumption | 750 |
| Protection Grade | IP40 |
| Operating Temp/Humidity | -20 ~ +40/10 ~ 90 |
| Storage Temp/Humidity | -40 ~ +60/10 ~ 80 |
| Lifetime (Normal Temp) | 50000 |
| Certifications | CE, RoHS,TUV-CE,TUV-LVD |



Indoor SMD HD

Slim, light weight stage displays

Cutting edge technology designed to simplify installation and maintenance procedures

Flight cases included for convenient storage and transport



Fanless design reduces noise levels and dust build up

Efficient heat dissipation improves longevity and power consumption

